

SHENZHEN JIZAN TECHNOLOGY CO.,LTD

www.jizankj.com



V9000P SPECIFICATION

Structural Parameter

Dimensions	170mm(L) X 78mm(W) X 17.4mm(D)
Weight	<286g
Display Screen	5.5-inch high definition full display(18:9),IPS LTPS 1440*720
Expand Port	2 Nano-SIM Card, Micro SD (TF) Card
Interfaces	USB3.0 Device,Type-C,OTG,extended thimble
Input Mode	Standard Handwriting, touch input or virtual keyboard input
Battery Capacity	Rechargeable Li-polymer Battery 3.8V 4600mAh
Speaker	Support
Key	1 power key,3 scan keys,2 volume keys,1 PTT key,1 menu key,1 return key

Performance Parameter

OS	Android 9.0
CPU	Qualcomm 2.0GHz Octa-core
RAM+ROM	2GB +16GB/ 4GB +64GB(optional)
Expansion	Micro SD/TF port (Max up to 128G)

Data Communication

WI-FI	Support 802.11 a/b/g/n/ac/d/e/h/i/k/r/v,2.4G/5G(optional) dual-band.IPV4.IPV6
FDD/TDD-LTE 4G	2G:GSM(850/900/1800/1900Mhz)
WCDMA 3G	3G:WCDMA(850/900/1900/2100Mhz)
GSM 2G	CDMA EVDO:BCO 4G: (B1/B3/B5/B7/B8/B20/B38/B39/B40/B41)

SHENZHEN JIZAN TECHNOLOGY CO.,LTD

www.jizankj.com

Bluetooth	Bluetooth 4.2/4.1+HS/4.0/3.0+HS/2.1+EDR
Standard Modules	
Camera	16MP autofocus rear camera with flash, 8MP front camera(optional)
GNSS	GPS/AGPS, GLONASS, BeiDou, Galileo, internal antenna
Operating Environment	
Operating	-20°C to 50°C
Storage Temperature	-40°C to 70°C
Environment Humidity	5%RH-95%RH(no condensation)
Drop Specifications	6 sides can bear impact from 1.5m drop to cement floor in the range of operating temperature
Roll Specifications	1000 times/0.5m, roll on 6 sides contact area
Sealed Environment	IP67
Barcode Scanning (OPTIONAL)	
2D SCANNER	Minde5600;Honeywell:N3603/N6603/N6703; Zebra:SE4710;
1D Symbologies	UPC/EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Codabar, MSI, RSS, etc.
2D Symbologies	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, JapanPostal Dutch Postal (KIX), etc.
NFC Reader (Optional)	
Frequency	13.56MHz
Protocol	ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2, etc.
Chips	M1 card(S50, S70), CPU card, NFC tags, etc.
Range	2-5cm
LF Reader(Optional)	
Frequency	125k/134.2k
Protocol	ISO11784/ISO11785; ISO18000-2(FDX-B)
Chips	EM4100、4200、TK4100、T5567/T5577、HITAG2、EM4305、
Range	2-5cm